## AUTOMATIC SLIDING GATE MOTOR



Powered by Alaska Automation Pvt. Ltd. **An ISO 9001:2015 Company** 



**Spring Limit** 



**Inside Design** 



**Copper Gear** 



Manually **Release Clutch** 



## Features:

- 1. Electronic soft-start.
- 2. Gate auto stop and re-open when an obstacle is encountered.
- 3. Auto close time can be adjusted from approximately 3 to 120 seconds.
- When power failure, use a allen key to release clutch, and push the door manually. 4.
- 5. Nicedesin, heavy duty working with copper motor (many supplier use allumium motor), copper worm gear.
- 6. Dc type can put transformer and back up battery inside.
- 7. The structure of integrated mechanic part and electronic part with built-in control panel, no any external controllers needed.
- 8. Intelligent automatic heating function Automatically increase the temperature when the temperature is below 0 degree.



**Copper Gear** 




Manually Release Clutch



**Spring Limit** 



Inside Design Copper Material



**Dimension** 



**Flashing Light** 



Metal Nylon Rack

## **Specification**

Model No	Eco 500	ECO 1000	ECO 1800
Weight of Gate	500 kg	1000kg	1800kg
Motor Speed	1350rpm	1600rpm	1620rpm
Motor Voltage	220Vac±110Vac	220Vac±110Vac	220Vac±110Vac
Material	Casting Aluminum Alloy	Casting Aluminum Alloy	Casting Aluminum Alloy
Reduction Ratio	23:1	23:1	23:1
Gear Speed	58.5RPM	65RPM	70RPM
Operating Speed	0.18M/S	0.18M/S	0.18M/S
Torque	22.5ncm	35ncm	35ncm
Frequency	50/60hz	50/60hz	50/60hz
Current	2A	4.5A	5.8A
Capacitor	18μf	20μf	60µf
Power	250w	250w	350w
Absorbed Power	440w	495w	594w
Manual Release	Key selector	Key selector	Key selector
Temperature	-40deg to 55deg	40deg to55deg	40deg to55deg
Humidity	5-90%	5-90%	5-90%

www.alaskagroup.in | sales@alaskagroup.in

Kindly Note: AAPL Reserve the rights to make changes at any stage without any prior notice. Color & Shape may be changed from time to time.